



Artificial Lift Services

www.Q2als.com

Q2-COMBO PLUNGER

Q2-Combo Plunger is designed to pump fluids more efficiently by cleaning barrel area and providing seal contact. It is recommended for high abrasive and cold production wells.

FEATURES & ADVANTAGES

- Spray metal coated plunger protects against corrosion and wear.
- Plunger has 0.005" fit size to allow trash to pass by the plunger.
- PA rings help to lift sand, trash and scale through the barrel.
- PolyPak rings provide excellent seal.

SPECIFICATIONS

- Plunger is manufactured from 1026 Carbon Steel tubing material with 10 PA rings and 1 PolyPak per end.
- Plunger is spray metal coated with Nickel or Tungsten Carbide.
- Minimum thickness of spray metal is 0.010 in. per side.

Pump Bore (in.)	Part Number			Plunger OD (in.)	Thread Size
	Plunger	PA Ring	PolyPak Ring		
1-1/4	105D20-SP	105RD-X	11310-N	1.250	1.0000-14
1-1/2	105F20-SP	105RF-X	12310-N	1.500	1.2500-14
1-3/4	105H20-SP	105RH-X	12310A-N	1.750	1.4704-14
2	105K20-SP	105RK-X	32310A-N	2.000	1.5604-14
2-1/4	105M20-SP	105RM-X	32310B-N	2.250	1.8024-14
2-1/2	105N20-SP	105RN-X	32310-N	2.500	2.1095-11.5
2-3/4	105P20-SP	105RP-X	32310C-N	2.750	2.1095-11.5

"X" in ring part number represents type of material

